



## Heavyduty Block, Single Sheave (with Bearing)

### Materials: Special Stainless steel

(Sheave pin, Swivel pin & arm pin are SUS304 grade stainless steel, Zerk fitting is brass)

- The working load corresponds to the working load of the bearings.
- This product contains one steel bearing with rubber seal.
- Nut in the center of the main body is left-hand thread.
- Working load limit does not apply to the becket.
- Safety working load is set variously in each country.

Safe working load is decided around from 1/8 to 1/10 of their breaking load.

Applications:  
**Topping and Vanging**

Model	S H E A V E DIA (MM)	SHEAVE QTY	Max Rope (mm)	Dia	WEIGHT	W o r k i n g Load Limit
AK1732 (P/N 93486)	125	1	20		12.8 lbs	2.5 (tons)
AK1733	150	1	20		20.9 lbs	3.0 (tons)
AK1734	175	1	24		31.1 lbs	3.5 (tons)



## Tough Block type PB (with Bearing) PAT.

### Materials: Special Stainless Steel

Sheave pin & neck bolt are SUS304 grade stainless steel

- The working load corresponds to the working load of the bearings.
- This product contains one steel bearings with rubber seal.
- Nut in the center of the main body is left-hand thread.
- Working load limit does not apply to the becket.
- Safety working load is set variously in each country.

Safe working load is decided around from 1/8 to 1/10 of their breaking load.

Applications:  
**Topping and Vanging**

Model	S H E A V E DIA (MM)	SHEAVE QTY	Max	Rope (mm)	Dia	WEIGHT	W o r k i n g Load Limit
AK10010 (P/N 93487)	125	1		20		13.7 lbs	3 (tons)
AK10011	150	1		20		20.7 lbs	5 (tons)
AK10012	175	1		24		31.8 lbs	6 (tons)



## AK Block Type 3-A, Single / Double Sheave (with Eye Top) PAT.

### Materials: Special Stainless Steel

Sheave and Swivel: SCS13 (Equal to SUS304 grade stainless steel), Side plate, Sheave pin, Hex. socket set screw are SUS304 grade stainless steel.

- Working load limit does not apply to the becket.
- Safety working load is set variously in each country.

Safe working load is decided around from 1/8 to 1/10 of their breaking load.

Applications:  
**Rope Rigging**  
**Picking Boom**  
**General Purpose**

Model	S H E A V E DIA (MM)	SHEAVE QTY	Max Rope (mm)	Dia	WEIGHT	W o r k i n g Load Limit
AK10143 (P/N 93485)	125	1	25		8.2 lbs	1200 (kg)
AK10148	150	2	25		12.1 lbs	1200 (kg)